


w131 Bell



Technical information

| | |
|-------------------------|--|
| Physical | |
| Material | Shade: die-cast aluminium Canopy: polyamide |
| Optics | Lens: PMMA Reflector: polycarbonate |
| IP rating | 20 |
| Protection class | II |

| | |
|---|----------------|
| LED | |
| Light source | PAR16 – GU10 |
| Lifetime expectancy | L70 / 25,000 h |
| CRI Colour rendering index | 90 |
| Stand. deviation of colour | 3-step MacAdam |
| Replaceable light source by end-user | |

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The applicable General Terms & Conditions apply.

Article-specific information

| | |
|---|--|
| Mounting | Ceiling suspended |
| LED Colour temperature (CCT) / Luminous flux | 2700 K / 437 lm 3000 K / 457 lm |
| Voltage / System power | 110–240 V / 6.5 W |
| Light control | Phase-cut dim |
| Net weight | 0.6 kg |
| Packaging dimensions | Box 1: L16 × W16.5 × H16 cm (0.005 m ³) Box 2: L5.5 × W5.5 × H6.7 cm (0.0002 m ³) |
| Gross weight | Box 1: 1 kg Box 2: 0.1 kg |

| | | |
|--|---|-----------------------------|
| 2700 K Colour temperature (CCT) | | Art. No. / EAN code |
| Traffic white (RAL 9016) | ● | 131S1901627 / 7330492002323 |
| Jet black (RAL 9005) | ● | 131S1900527 / 7330492002255 |
| Silver grey (similar to RAL 9006) | ● | 131S1111127 / 7330492002231 |
| Pure orange (RAL 2004) | ● | 131S1200427 / 7330492002248 |
| Zink yellow (RAL 1018) | ● | 131S1101827 / 7330492002262 |
| Beige (RAL 1001) | ● | 131S1100127 / 7330492002279 |
| Traffic red (RAL 3020) | ● | 131S1302027 / 7330492002286 |
| Sapphire blue (RAL 5003) | ● | 131S1500327 / 7330492002293 |
| Grass green (RAL 6010) | ● | 131S1601027 / 7330492002309 |
| Sepia brown (RAL 8014) | ● | 131S1801427 / 7330492002316 |

| | | |
|--|---|-----------------------------|
| 3000 K Colour temperature (CCT) | | Art. No. / EAN code |
| Traffic white (RAL 9016) | ● | 131S1901630 / 7330492002422 |
| Jet black (RAL 9005) | ● | 131S1900530 / 7330492002354 |
| Silver grey (similar to RAL 9006) | ● | 131S1111130 / 7330492002330 |
| Pure orange (RAL 2004) | ● | 131S1200430 / 7330492002347 |
| Zink yellow (RAL 1018) | ● | 131S1101830 / 7330492002361 |
| Beige (RAL 1001) | ● | 131S1100130 / 7330492002378 |
| Traffic red (RAL 3020) | ● | 131S1302030 / 7330492002385 |
| Sapphire blue (RAL 5003) | ● | 131S1500330 / 7330492002392 |
| Grass green (RAL 6010) | ● | 131S1601030 / 7330492002408 |
| Sepia brown (RAL 8014) | ● | 131S1801430 / 7330492002415 |

| | |
|-----------------------------|----------------------------|
| Accessories | Art. No. / EAN code |
| 1-phase track adapter white | ACC00102 / 7330492001920 |
| 1-phase track adapter black | ACC00105 / 7330492001937 |
| 3-phase track adapter white | ACC00202 / 7330492001944 |
| 3-phase track adapter black | ACC00205 / 7330492001951 |